## **Special solutions**

## IDE//\L

## High performance high security shredders

For hard drives, smart cards and optical media



## **Special solutions**







Hard drive punch	0101 HDP	High security shredder for smart cards and optical media	0103 SCD
For discarded hard drives from	PCs / notebooks / printers / copiers	For all types of cards	with chip or magnetic stripe
Suitable for hard drive sizes	2.5" / 3.5"	For all types of CDs and DVDs	•
Security level ISO / IEC 21964 (DIN 66399)	H-3	Shredder type	particles
Adjustable feed chute constructed of high quality steel	•	Particle size, mm	2.2 x 4 mm
Single feed	•	Shred performance (cards/CDs/DVDs)	up to 2.500 per hou
Punching die from hardened, nickel-plated steel	•	One by one feeding (feed slot)	•
Robust end plate	•	Security level ISO / IEC 21964 (DIN 66399)	T-6, E-5, O-5
Destroys mechanical components, PC board and hard disc	•	Solid steel cutting shafts made of special hardened steel	•
Punching cycle (per hard drive)	15 seconds	Meets North American NSA/CSS 04-02 requirements <sup>2</sup>	•
LEDs for illuminating the feed chute	•	Volume of antistatic collection bin, litres	100
Slider mechanism for unloading punching compartment	•	High-quality wooden cabinet, mobile on castors	•
Sturdy plastic bin for destroyed hard drives	•	Power connection, volts / Hz (single phase) <sup>1</sup>	230 / 50 / 1~
Collection bin with weight sensor	•	Motor capacity, W	1600
High-quality wooden cabinet, mobile on castors	•	Automatic start/stop via photo cell	•
Power connection, volts / Hz (single phase) <sup>1</sup>	230 / 50 / 1~	ECC – Electronic Capacity Control	•
Motor capacity, W	640	Automatic oil injection on the cutting shafts	•
Suitable for continuous operation	•	Suitable for continuous operation	•
Control element for start and stop	EASY-SWITCH	Control element	EASY-SWITCH
SPS Safety Protection System:	•	SPS Safety Protection System:	•
– Hinged safety flap for the feed chute	•	- Safety flap (to prevent particle "fly back")	electronic
– Jam protection for punching die with automatic reverse	•	- Automatic reverse and power cut-off (to prevent jams)	•
- Automatic stop after punching process	•	- Automatic stop if collection bin is full	•
– Automatic shut-off when the collection bin is full	•	- Electronic door protection	•
- Electronic door protection	•	– Double motor protection	•
– Double motor protection	•	– Energy saving mode	•
Dimensions, mm (H x W x D)	850 x 495 x 470	Dimensions, mm (H x W x D)	1020 x 548 x 590
Weight, kg	63	Weight, kg	105